

EPSON Professional Media

Smooth Fine Art Paper

For Use With:

EPSON Stylus® Pro 7500
EPSON Stylus Pro 9500

Product Information

Artist and professional photographers require archival print media for their digital fine art and photography. Now, in conjunction with our new EPSON Archival™ Ink, we bring you this acid free, 100% cotton rag fine art paper. Available in 225 g/m² rolls for flexibility and 425 g/m² sheets for a museum quality feel, this bright white hot press paper has the look and touch of Old World handmade paper. Capable of creating 1440 dpi, high-resolution prints this paper yields brilliant colors and deep blacks. The paper is made exclusively for Epson by Crane & Co., makers of fine specialty papers since 1801.

Like all of Epson's innovative media, this paper is engineered to give you the highest resolution and color saturation possible. Epson's printer driver software actually optimizes the amount of ink released onto the page, based on the type of paper used. As always, EPSON supplies guarantee EPSON quality.



Features/Benefits

- Acid free to preserve fine art and photos
- 100% cotton rag for long term durability
- Bright white surface for vivid color reproduction
- Rich black images for prints with exceptional contrast
- Smooth surface for sharp details and accurate reproduction
- 425 g/m² basis weight for museum quality appearance (sheets)
- 225 g/m² basis weight on rolls for versatility (rolls)
- Flat matte surface to eliminate glare
- 1440 dpi printing for high-quality output
- Dries instantly for easy handling with Epson inks

Feature Checklist

Feature	Performance	Additional Comments
Indoor/outdoor usage	Indoor only	
Lightfastness	200 years (only when using EPSON Archival Inks)	Lightfastness ratings are based on accelerated testing of prints on specialty media, displayed indoors, under glass. Lightfastness only estimates the life of the ink, not the media.
Archivability	Excellent	To provide the best protection, keep prints behind a glass plate or Plexiglas shield with UF3.
Resistance to water	Good	Bleeding does not occur with incidental water contact. However, try to prevent exposure to moisture.
Ink drying time	Immediate (less than 30 seconds)	Ink is dry to the touch after printing. However, it takes 24 hours before it cures and becomes durable.
Handling requirements	Use gloves	Use gloves when handling the paper to avoid smudges and fingerprints on the printing surface.
Mounting feasibility	Recommended	Use rag board or other high quality, acid-free mounting materials.
Lamination feasibility	Not recommended	If a protective coating is desired, use a fast-drying, acrylic spray with a UV absorbent.

NOTE: Actual print stability and longevity will vary according to image, display conditions, light intensity, humidity, atmospheric conditions, and post-printing treatments. Epson does not guarantee stability or longevity. For maximum print life, display all prints under glass or lamination or properly store them.



Professional Media Smooth Fine Art Paper

Technical Specifications

	Rolls	Sheets
Basis weight	225 g/m ²	425 g/m ²
Thickness	15 mil	27 mil
ISO brightness	89%	89%
Opacity	98%	99%
Hot lamination	No	No
Base material	100% Cotton rag	100% Cotton rag
Surface finish	Smooth, hot press matte	Smooth, hot press matte
Core size	3"	N/A
Spindle	3" high-tension ¹	N/A

¹Optional printer accessory, available from Epson
EPSON Stylus Pro 9500, Part No. C811052
EPSON Stylus Pro 7500, Part No. C811103

Driver Settings

Printer driver	Watercolor Paper–Radiant White
5100 v1.5 RIP	Watercolor Paper–RW 720 x 720
	Watercolor Paper–RW 1440 x 720

Operating Specifications

Required temperature for optimum performance	60° - 80° F 15° - 25° C
Required humidity for optimum performance	40% - 60% RH
(Note: High humidity will prolong the drying time for lamination purposes.)	

Ordering Specifications

Product code	SO41431 (24" x 50')
Individual box UPC code	0-10343-83307-4
Product code	SO41432 (36" x 50')
Individual box UPC code	0-10343-83308-1
Product code	SO41433 (44" x 50')
Individual box UPC code	0-10343-83309-8
Product code	SO41434 (24" x 30"/20 sheets)
Individual box UPC code	0-10343-83310-4
Product code	SO41435 (36" x 44"/10 sheets)
Individual box UPC code	0-10343-83311-1

Packing Specifications

SO41431	Individual box dimensions	25.75" x 6.25" x 6.25"
	Individual box weight	8.5 lb
	Pallet quantity	72
SO41432	Individual box dimensions	37.88" x 6.25" x 6.25"
	Individual box weight	11.5 lb
	Pallet quantity	56
SO41433	Individual box dimensions	45.75" x 6.25" x 6.25"
	Individual box weight	14.5 lb
	Pallet quantity	48
SO41434	Individual box dimensions	33.25" x 26.5" x 11.13"
	Individual box weight	10.0 lb
	Pallet quantity	25
SO41435	Individual box dimensions	47.25" x 38.63" x 0.94"
	Individual box weight	20.0 lb
	Pallet quantity	25

MSRP*	Per Unit	Per Square Foot
SO41431	\$179.00	\$1.79
SO41432	269.00	1.79
SO41433	329.00	1.79
SO41434	229.00 (20 sheets)	2.29
SO41435	249.00 (10 sheets)	2.26

* Actual prices may vary.

YOU'VE GOT TO SEE IT IN



COLOR.™

www.epson.com

Epson America, Inc.
3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.
550 McNicoll, Willowdale, Ontario M2H 2E1

Epson Latin America
6303 Blue Lagoon Drive, Miami, FL 33126

Specifications are subject to change without notice. EPSON and EPSON Stylus are registered trademarks of Seiko Epson Corporation. EPSON Archival is a trademark of Epson America, Inc. All other products and brand names are registered trademarks of their respective companies. Epson disclaims any and all rights in these marks.
Copyright 2001 Epson America, Inc. CPD-10291 5K 1/01 CL

Printed on Recycled Paper